



Cell Characteristics

Material	LiFePO ₄ / AG,	
Capacity	Nominal	157 Ah
		502.4 Wh
Energy	Typical	159 Ah
		508.8 Wh
Cell Voltage	Nominal	3.2 V
	Charge	3.65 V
	Discharge	2.5 V
		2.0 V (≤0°C)
Charge Current	Standard	78.5 A
	Maximum	157 A (1.0C)
Charge Time	Standard	2 hour
Discharge Current	Standard	78.5 A
	Maximum	235.5 A (1.5C)
Temperature	Charge	0°C to 55°C
	Discharge	-20°C to 60°C
Energy Density	Volumetric	359 Wh/L
	Gravimetric	165 Wh/kg
Typical Impedance	AC (1000HZ)	≤0.6 mΩ
	DC (50%SOC)	0.9 mΩ
Cycle Life	0.5C/0.5C, 80%DOD @25°C	
	≥6000, 80%EOL	
Weight	3.04±0.1 Kg	
Safety Standard	UL 、 UN 、 IEC 、 GB/T	


Physical Characteristics




Charge Rate Characteristics




Discharge Rate Characteristics



Discharge at Different Temperature



Cycle Characteristics



*The information contained herein is for reference only. For more information please contact BAK sales.

Shenzhen BAK Power Battery Co., Ltd.

☎ 0755-61886818

✉ Info@bak.com.cn

📍 BAK Industrial Park, Kuiyong, Dapeng New District.

📍 No.9 Keyan Road Nanshan District, Shenzhen

Fuzhou BAK Battery Co., Ltd.

☎ 0794-8333611

✉ Info@bak.com.cn

📍 No.4002 Wenchang Road, High-Tech Industrial Development Zone, Fuzhou Jiangxi